Trane Two-Stage Furnace Control for Variable Speed Blower & Inducer Motors

50V54-820



Direct OEM replacement for 80V or 120V ignitor applications



Direct OEM Replacement

Fast drop-in OEM mounting for XV95 furnaces Includes 120V ignitor and harness to service 80V and 120V applications

Detailed installation instructions



Advanced Diagnostics

LED fault recall and status codes



Complete Cross Reference

Extensive and up-to-date cross reference by OEM model number





50V54-820 replaces previous model 50V64-743



Trane Two-Stage Furnace Control for Variable Speed Blower and Inducer Motors

50V54-820 Direct OEM replacement for 80V or 120V ignitor applications

SPECIFICATIONS:

Electrical Ratings:

Input Voltage: 25VAC, 60 Hz

Max Input Current: @ 25VAC 525 mA + MV

Inducer Output: 3 Phase

Relay Contact Ratings:

Gas Valve Relay: 1.5A @ 30 VAC, 0.6 pf

Ignitor Relay: 2.0A @ 120 VAC Humidifier Load: 1.0A @ 120 VAC

Electronic Air Cleaner Load: 1.0A @ 120 VAC

Flame Current Requirements:

Min current to insure flame detection: $1.0 \,\mu\text{A}\,\text{DC}^*$ Max current for non-detection: $0.1 \,\mu\text{A}\,\text{DC}^*$ Max allowable leakage resistance: $100 \,\text{M}$ ohms * Measured with a DC microammeter in series with the flame probe lead

Timing Specifications:

(All times are in seconds unless noted otherwise)

Ignition warm-up	Ignition activation period	Heat ON delay	Post-purge	Blower OFF delay	Cooling ON delay
20	2	45	5	60/100*/140/180	0

^{*} Denotes factory default

50V54-820 CROSS REFERENCE REPLACEMENT:

_		
Trane/American	D342062P01	White-Rodgers
Standard Brands	D342263P01	50V54-507
CNT03777	D342263P02	50V54-571
CNT04678	D342263P03	50V54-820
CNT04985	D342263P04	50V64-495
CNT05160	D343687P01	50V64-507
CNT06017	D343687P02	50V64-743
CNT06585	KIT15816	

Operating Temperature Range:

-40° to 176° F (-40° to 80° C)

Humidity Range:

5 to 95% relative humidity (non-condensing)

Agency Approvals:

CSA - USA/Canada

Gases Approved:

Natural, Manufactured, Mixed, Liquefied Petroleum, and LP Gas-Air Mixtures are all approved for use

1 Year Limited Warranty

TRANE OEM DIRECT REPLACEMENT 120V IGNITOR

789A-820

Included in furnace control kit but also sold separately

- Ignitor with OEM wiring plug connector
- Trane mounting bracket plus screws





Replaces Trane models:

- D156805P01
- IGN00146
- IGN00152

